AllBarcodes_Basic.aspx

```
<%@ Page Language="C#" AutoEventWireup="true" CodeFile="AllBarcodes_Basic.aspx.cs"
    Inherits="AllBarcodes_Basic" MaintainScrollPositionOnPostback="true" %>

<%@ Register Assembly="ceTe.DynamicBarcode.Creator.40" Namespace="ceTe.DynamicBarcode.Creator.Web"
    TagPrefix="cc1" %>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head id="Head1" runat="server">
    <title>DynamicBarcode Creator Examples</title>
    <link rel="stylesheet" type="text/css" href="Style/DynamicBarcodeCreator.css" />
    <meta name="DESCRIPTION" content="All Barcode Example in C# using DynamicBarcode Creator v2.0 for .NET" />
    <style type="text/css">
        .style1
        {
            width: 101px;
        }
    </style>
</head>
<body>
    <div id="banner">
        <img alt="DynamicBarcode Creator" height="85px" width="74px" src="Images/DynamicBarcodeCreator.png"
            align="right" /><img height="26px" width="156px" alt="ceTe Software" src="Images/ceTeSoftware_top.gif" />
        <div id="header">
            <i>DynamicBarcode Creator </i> v2.0 for .NET Examples</div>
        <h1>
            All Barcodes Example
        </h1>
    </div>
    <div id="content">
        <form id="form1" runat="server">
        <table border="0">
            <tr class="head">
                <td style="width: 25%; height: 20px">
                    Barcode Type
                </td>
                <td style="width: 25%; height: 20px">
                    Data
                </td>
                <td style="width: 50%; height: 20px">
                    Barcode Using Controls
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    UPC/EAN/JAN Barcodes
                </td>
            </tr>
            <tr>
                <td>
```

```
                    EAN 13 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtEan13" runat="server" Text="123456789012"></asp:TextBox>
                    <asp:Button ID="btnUpdateEan13" runat="server" Text="Update" OnClick="btnUpdateEan13_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan13" runat="server" LinearBarcodeType="Ean13"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789012" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 13, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup2" runat="server" Text="123456789012"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup2Sup" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateEan132" runat="server" Text="Update" OnClick="btnUpdateEan132_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan132" runat="server" LinearBarcodeType="Ean13Supplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789012" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
```

```
                    EAN 13, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup5" runat="server" Text="123456789012"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateEan135" runat="server" Text="Update" OnClick="btnUpdateEan135_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan135" runat="server" LinearBarcodeType="Ean13Supplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789012" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 8 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtEan8" runat="server" Text="12345670"></asp:TextBox>
                    <asp:Button ID="btnUpdateEan8" runat="server" Text="Update" OnClick="btnUpdateEan8_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan8" runat="server" LinearBarcodeType="Ean8"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345670" />
                </td>
            </tr>
            <tr>
                <td>
```

```
                    EAN 8, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup2" runat="server" Text="12345670"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup2Sup" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateEan82" runat="server" Text="Update" OnClick="btnUpdateEan82_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan82" runat="server" LinearBarcodeType="Ean8Supplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345670" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 8, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup5" runat="server" Text="12345670"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
```

```
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateEan85" runat="server" Text="Update" OnClick="btnUpdateEan85_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan85" runat="server" LinearBarcodeType="Ean8Supplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345670" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version A Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtUpcA" runat="server" Text="12345678901"></asp:TextBox>
                    <asp:Button ID="btnUpdateUpcA" runat="server" Text="Update" OnClick="btnUpdateUpcA_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcA" runat="server" LinearBarcodeType="UpcA"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345678901" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version A, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup2" runat="server" Text="12345678901"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
```

```
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup2Sup" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpcA2" runat="server" Text="Update" OnClick="btnUpcA2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcA2" runat="server" LinearBarcodeType="UpcASupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345678901" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version A, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup5" runat="server" Text="12345678901"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpcA5" runat="server" Text="Update" OnClick="btnUpcA5_Click" />
                            </td>
```

```
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcA5" runat="server" LinearBarcodeType="UpcASupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345678901" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version E Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtUpcE" runat="server" Text="0123456"></asp:TextBox>
                    <asp:Button ID="btnUpdateUpcE" runat="server" Text="Update" OnClick="btnUpdateUpcE_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcE" runat="server" LinearBarcodeType="UpcE"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="0123456" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version E, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup2" runat="server" Text="0123456"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup2Sup" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateUpcE2" runat="server" Text="Update" OnClick="btnUpdateUpcE2_Click" />
                            </td>
```

```
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcE2" runat="server" LinearBarcodeType="UpcESupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="0123456" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version E, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup5" runat="server" Text="0123456"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateUpcE5" runat="server" Text="Update" OnClick="btnUpdateUpcE5_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcE5" runat="server" LinearBarcodeType="UpcESupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="0123456" SupplementValue="12345" />
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    Postal Barcodes
                </td>
            </tr>
```

```
            <tr>
                <td>
                    Australia Post Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtAustraliaPost" runat="server" Text="1112345678"></asp:TextBox>
                    <asp:Button ID="btnUpdateAustraliaPost" runat="server" Text="Update" OnClick="btnUpdateAustraliaPost_Click"
/>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeAustraliaPost" runat="server" LinearBarcodeType="AustraliaPost"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1112345678" />
                </td>
            </tr>
            <tr>
                <td>
                    Deutsche Post Identcode Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtDeutschePostIdentcode" runat="server" Text="12345678901"></asp:TextBox>
                    <asp:Button ID="btnDeutschePostIdentcode" runat="server" Text="Update"
OnClick="btnDeutschePostIdentcode_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeDeutschePostIdentcode" runat="server" SymbolHeight="80"
                        LinearBarcodeType="DeutschePostIdentcode" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="12345678901" />
                </td>
            </tr>
            <tr>
                <td>
                    Deutsche Post Leitcode Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtDeutschePostLeitcode" runat="server" Text="1234567890123"></asp:TextBox>
                    <asp:Button ID="btnDeutschePostLeitcode" runat="server" Text="Update"
OnClick="btnDeutschePostLeitcode_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeDeutschePostLeitcode" runat="server" SymbolHeight="80"
                        LinearBarcodeType="DeutschePostLeitcode" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="1234567890123" />
                </td>
            </tr>
            <tr>
                <td>
                    Intelligent Mail Barcode
                </td>
                <td>
```

```
                    <asp:TextBox ID="txtIntelligentMail" runat="server" Text="01234567094987654321012345678911"></asp:TextBox>
                    <asp:Button ID="btnUpdateIntelligentMail" runat="server" Text="Update"
OnClick="btnUpdateIntelligentMail_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIntelligentMail" runat="server"
LinearBarcodeType="IntelligentMailBarcode"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="01234567094987654321012345678911" />
                </td>
            </tr>
            <tr>
                <td>
                    KIX Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtKix" runat="server" Text="1231FZ13XHS"></asp:TextBox>
                    <asp:Button ID="btnKix" runat="server" Text="Update" OnClick="btnKix_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeKix" runat="server" LinearBarcodeType="Kix"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1231FZ13XHS" />
                </td>
            </tr>
            <tr>
                <td>
                    Postnet Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtPostnet" runat="server" Text="20815470412"></asp:TextBox>
                    <asp:Button ID="btnUpdatePostnet" runat="server" Text="Update" OnClick="btnUpdatePostnet_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodePostnet" runat="server" LinearBarcodeType="Postnet"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="20815470412" />
                </td>
            </tr>
            <tr>
                <td>
                    RM4SCC Royal Mail Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtRm4scc" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnUpdateRm4scc" runat="server" Text="Update" OnClick="btnUpdateRm4scc_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeRm4scc" runat="server" LinearBarcodeType="Rm4scc"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
```

```
            <tr>
                <td>
                    Singapore Post Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtSingaporePost" runat="server" Text="208154"></asp:TextBox>
                    <asp:Button ID="btnSingaporePost" runat="server" Text="Update" OnClick="btnSingaporePost_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeSingaporePost" runat="server" LinearBarcodeType="SingaporePost"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="208154" />
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    ISBN/ISMN/ISSN Barcodes
                </td>
            </tr>
            <tr>
                <td>
                    ISBN Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtIsbn" runat="server" Text="987123456789"></asp:TextBox>
                    <asp:Button ID="btnIsbn" runat="server" Text="Update" OnClick="btnIsbn_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsbn" runat="server" LinearBarcodeType="Isbn"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="987123456789" />
                </td>
            </tr>
            <tr>
                <td>
                    ISBN, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsbn2Value" runat="server" Text="987123456789"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
```

```
                            <td>
                                <asp:TextBox ID="txtIsbnSup2Value" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIsbnSup2" runat="server" Text="Update" OnClick="btnIsbnSup2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsbnSup2" runat="server" LinearBarcodeType="IsbnSupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="987123456789" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    ISBN, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsbn5Value" runat="server" Text="987123456789"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsbnSup5Value" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIsbnSup5" runat="server" Text="Update" OnClick="btnIsbnSup5_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
```

```
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsbnSup5" runat="server" LinearBarcodeType="IsbnSupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="987123456789" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    ISMN Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtIsmn" runat="server" Text="979-0-1234-5678"></asp:TextBox>
                    <asp:Button ID="btnIsmn" runat="server" Text="Update" OnClick="btnIsmn_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsmn" runat="server" LinearBarcodeType="Ismn"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="979-0-1234-5678" />
                </td>
            </tr>
            <tr>
                <td>
                    ISMN, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsmn2Value" runat="server" Text="979-0-1234-5678"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsmnSup2Value" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIsmnSup2" runat="server" Text="Update" OnClick="btnIsmnSup2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
```

```
633                 <td style="width: 193px">
634                     <cc1:LinearBarcode ID="dynamicBarcodeIsmnSup2" runat="server" LinearBarcodeType="IsmnSupplement2"
635                         Dpi="96" BarcodeMargin="20,20,20,20" Text="979-0-1234-5678" SupplementValue="12" />
636                 </td>
637             </tr>
638             <tr>
639                 <td>
640                     ISMN, 5 Digit Supplement Barcode
641                 </td>
642                 <td>
643                     <table class="propTable">
644                         <tr>
645                             <td>
646                                 Value :
647                             </td>
648                             <td>
649                                 <asp:TextBox ID="txtIsmn5Value" runat="server" Text="979-0-1234-5678"></asp:TextBox>
650                             </td>
651                         </tr>
652                         <tr>
653                             <td>
654                                 Supplement :
655                             </td>
656                             <td>
657                                 <asp:TextBox ID="txtIsmnSup5Value" runat="server" Text="12345"></asp:TextBox>
658                             </td>
659                         </tr>
660                         <tr>
661                             <td>
662                             </td>
663                             <td style="padding-left: 120px;">
664                                 <asp:Button ID="btnIsmnSup5" runat="server" Text="Update" OnClick="btnIsmnSup5_Click" />
665                             </td>
666                         </tr>
667                     </table>
668                 </td>
669                 <td style="width: 193px">
670                     <cc1:LinearBarcode ID="dynamicBarcodeIsmnSup5" runat="server" LinearBarcodeType="IsmnSupplement5"
671                         Dpi="96" BarcodeMargin="20,20,20,20" Text="979-0-1234-5678" SupplementValue="12345" />
672                 </td>
673             </tr>
674             <tr>
675                 <td>
676                     ISSN Barcode
677                 </td>
678                 <td>
679                     <asp:TextBox ID="txtIssn" runat="server" Text="977-1234-56700"></asp:TextBox>
680                     <asp:Button ID="btnIssn" runat="server" Text="Update" OnClick="btnIssn_Click" />
681                 </td>
```

```
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIssn" runat="server" LinearBarcodeType="Issn"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="977-1234-56700" />
                </td>
            </tr>
            <tr>
                <td>
                    ISSN, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIssn2Value" runat="server" Text="977-1234-56700"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIssnSup2Value" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIssnSup2" runat="server" Text="Update" OnClick="btnIssnSup2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIssnSup2" runat="server" LinearBarcodeType="IssnSupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="977-1234-56700" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    ISSN, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
```

```
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIssn5Value" runat="server" Text="977-1234-56700"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIssnSup5Value" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIssnSup5" runat="server" Text="Update" OnClick="btnIssnSup5_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIssnSup5" runat="server" LinearBarcodeType="IssnSupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="977-1234-56700" SupplementValue="12345" />
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    Other Linear Barcodes
                </td>
            </tr>
            <tr>
                <td style="height: 39px">
                    Codabar Barcode
                </td>
                <td style="height: 39px">
                    <asp:TextBox ID="txtCodabar" runat="server" Text="A1234D"></asp:TextBox>
                    <asp:Button ID="btnUpdateCodabar" runat="server" Text="Update" OnClick="btnUpdateCodabar_Click" />
                </td>
                <td style="width: 193px; height: 39px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCodabar" runat="server" SymbolHeight="80" LinearBarcodeType="Codabar"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="A1234D" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 11 Barcode
```

```
                </td>
                <td>
                    <asp:TextBox ID="txtCode11" runat="server" Text="1234567"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode11" runat="server" Text="Update" OnClick="btnUpdateCode11_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode11" runat="server" SymbolHeight="80" LinearBarcodeType="Code11"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 128 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode128" runat="server" Text="Hello World"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode128" runat="server" Text="Update" OnClick="btnUpdateCode128_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode128" runat="server" SymbolHeight="80" LinearBarcodeType="Code128"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="Hello World" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 25 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode25" runat="server" Text="123456789"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode25" runat="server" Text="Update" OnClick="btnUpdateCode25_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode25" runat="server" SymbolHeight="80" LinearBarcodeType="Code25"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 39 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode39" runat="server" Text="123456789"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode39" runat="server" Text="Update" OnClick="btnUpdateCode39_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode39" runat="server" SymbolHeight="80" LinearBarcodeType="Code39"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789" />
                </td>
            </tr>
```

```
            <tr>
                <td>
                    Code 93 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode93" runat="server" Text="123456789"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode93" runat="server" Text="Update" OnClick="btnUpdateCode93_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode93" runat="server" SymbolHeight="80" LinearBarcodeType="Code93"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 14 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtEan14" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnEan14" runat="server" Text="Update" OnClick="btnEan14_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan14" runat="server" SymbolHeight="80" LinearBarcodeType="Ean14"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    GS1 DataBar
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td class="style1">
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtGS1DataBar" runat="server" Text="(01)1234567890123"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                                GS1 Type :
                            </td>
                            <td>
                                <asp:DropDownList ID="ddlGS1Type" runat="server">
                                    <asp:ListItem Selected="True" Text="Omnidirectional" Value="Omnidirectional"></asp:ListItem>
                                    <asp:ListItem Text="Limited" Value="Limited"></asp:ListItem>
                                    <asp:ListItem Text="Expanded" Value="Expanded"></asp:ListItem>
```

```
                                </asp:DropDownList>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateGS1" runat="server" Text="Update" OnClick="btnUpdateGS1_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeGS1" runat="server" LinearBarcodeType="GS1DataBar"
                        GS1DataBarType="Omnidirectional" SymbolHeight="80" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="(01)1234567890123" />
                </td>
            </tr>
            <tr>
                <td>
                    IATA 25 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtIata25" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnIata25" runat="server" Text="Update" OnClick="btnIata25_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIata25" runat="server" SymbolHeight="80" LinearBarcodeType="Iata25"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    Interleaved 25 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtInterleaved25" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnUpdateInterleaved25" runat="server" Text="Update" OnClick="btnUpdateInterleaved25_Click"
/>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeInterleaved" runat="server" SymbolHeight="80"
                        LinearBarcodeType="Interleaved25" Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    ITF 14 Barcode
                </td>
```

```
                <td>
                    <asp:TextBox ID="txtItf14" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnItf14" runat="server" Text="Update" OnClick="btnItf14_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeItf14" runat="server" LinearBarcodeType="Itf14"
                        SymbolHeight="80" Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    MSI Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtMsiBarcode" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnUpdateMsi" runat="server" Text="Update" OnClick="btnUpdateMsi_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeMsi" runat="server" SymbolHeight="80" LinearBarcodeType="MsiBarcode"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    2D and Stacked GS1 Databar Barcodes
                </td>
            </tr>
            <tr>
                <td>
                    Stacked GS1 DataBar
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td class="style1">
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtStackedGs1" runat="server" Text="(01)1234567890123"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                                Stacked GS1 Type :
                            </td>
                            <td>
                                <asp:DropDownList ID="ddlStackedGS1" runat="server">
                                    <asp:ListItem Selected="True" Text="Stacked" Value="Stacked"></asp:ListItem>
                                    <asp:ListItem Text="Stacked Omnidirectional" Value="StackedOmnidirectional"></asp:ListItem>
```

```
                                    <asp:ListItem Text="Expanded Stacked" Value="ExpandedStacked"></asp:ListItem>
                                </asp:DropDownList>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateStackedGS1" runat="server" Text="Update"
OnClick="btnUpdateStackedGS1_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:StackedGS1DataBar ID="dynamicBarcodeStackedGS1" runat="server" StackedGS1DataBarType="Stacked"
                        RowHeight="50" Dpi="96" BarcodeMargin="20,20,20,20" />
                </td>
            </tr>
            <tr>
                <td>
                    Aztec Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtAztec" runat="server" Text="Hello World"></asp:TextBox>
                    <asp:Button ID="btnAztec" runat="server" Text="Update" OnClick="btnAztec_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:Aztec ID="dynamicBarcodeAztec" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Hello World" />
                </td>
            </tr>
            <tr>
                <td>
                    Data Matrix Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtDataMatrix" runat="server" Text="Data Matrix barcode for .NET can handle
overflow."></asp:TextBox>
                    <asp:Button ID="btnUpdateDataMatrix" runat="server" Text="Update" OnClick="btnUpdateDataMatrix_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:DataMatrix ID="dynamicBarcodeDataMatrix" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Data Matrix barcode for .NET can handle overflow." />
                </td>
            </tr>
            <tr>
                <td>
                    PDF417 Barcode
```

```
                </td>
                <td>
                    <asp:TextBox ID="txtPdf417" runat="server" Text="Hello World"></asp:TextBox>
                    <asp:Button ID="btnUpdatePdf417" runat="server" Text="Update" OnClick="btnUpdatePdf417_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:Pdf417 ID="dynamicBarcodePdf417" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Hello World" />
                </td>
            </tr>
            <tr>
                <td>
                    QR Code
                </td>
                <td>
                    <asp:TextBox ID="txtQRCode" runat="server" Text="Hello World"></asp:TextBox>
                    <asp:Button ID="btnUpdateQRCode" runat="server" Text="Update" OnClick="btnUpdateQRCode_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:QRCode ID="dynamicBarcodeQRCode" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Hello World" />
                </td>
            </tr>
        </table>
        </form>
    </div>
</body>
</html>
```

AllBarcodes_Basic.aspx.cs

```
using System;
using System.Collections.Generic;
using System.Web;
using System.Web.UI;
using System.Web.UI.WebControls;

public partial class AllBarcodes_Basic : System.Web.UI.Page
{
    protected void Page_Load(object sender, EventArgs e) { }

    protected void btnUpdateCode128_Click(object sender, EventArgs e)
    {
        dynamicBarcodeCode128.Text = txtCode128.Text;
    }

    protected void btnUpdateCodabar_Click(object sender, EventArgs e)
    {
        dynamicBarcodeCodabar.Text = txtCodabar.Text;
    }

    protected void btnUpdateCode25_Click(object sender, EventArgs e)
    {
        dynamicBarcodeCode25.Text = txtCode25.Text;
    }

    protected void btnUpdateCode39_Click(object sender, EventArgs e)
    {
        dynamicBarcodeCode39.Text = txtCode39.Text;
    }

    protected void btnUpdateDataMatrix_Click(object sender, EventArgs e)
    {
        dynamicBarcodeDataMatrix.Text = txtDataMatrix.Text;
    }

    protected void btnUpdateQRCode_Click(object sender, EventArgs e)
    {
        dynamicBarcodeQRCode.Text = txtQRCode.Text;
    }

    protected void btnUpdatePdf417_Click(object sender, EventArgs e)
    {
        dynamicBarcodePdf417.Text = txtPdf417.Text;
    }

    protected void btnUpdateIntelligentMail_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIntelligentMail.Text = txtIntelligentMail.Text;
    }
```

```
50
51      protected void btnUpdatePostnet_Click(object sender, EventArgs e)
52      {
53          dynamicBarcodePostnet.Text = txtPostnet.Text;
54      }
55
56      protected void btnUpdateRm4scc_Click(object sender, EventArgs e)
57      {
58          dynamicBarcodeRm4scc.Text = txtRm4scc.Text;
59      }
60
61      protected void btnUpdateInterleaved25_Click(object sender, EventArgs e)
62      {
63          dynamicBarcodeInterleaved.Text = txtInterleaved25.Text;
64      }
65
66      protected void btnUpdateMsi_Click(object sender, EventArgs e)
67      {
68          dynamicBarcodeMsi.Text = txtMsiBarcode.Text;
69      }
70
71      protected void btnUpdateEan13_Click(object sender, EventArgs e)
72      {
73          dynamicBarcodeEan13.Text = txtEan13.Text;
74      }
75
76      protected void btnUpdateEan132_Click(object sender, EventArgs e)
77      {
78          dynamicBarcodeEan132.Text = txtEan13Sup2.Text;
79          dynamicBarcodeEan132.SupplementValue = txtEan13Sup2Sup.Text;
80      }
81
82      protected void btnUpdateEan135_Click(object sender, EventArgs e)
83      {
84          dynamicBarcodeEan135.Text = txtEan13Sup5.Text;
85          dynamicBarcodeEan135.SupplementValue = txtEan13Sup5Sup.Text;
86      }
87
88      protected void btnUpdateEan8_Click(object sender, EventArgs e)
89      {
90          dynamicBarcodeEan8.Text = txtEan8.Text;
91      }
92
93      protected void btnUpdateEan82_Click(object sender, EventArgs e)
94      {
95          dynamicBarcodeEan82.Text = txtEan8Sup2.Text;
96          dynamicBarcodeEan82.SupplementValue = txtEan8Sup2Sup.Text;
97      }
98      protected void btnUpdateEan85_Click(object sender, EventArgs e)
```

```
    {
        dynamicBarcodeEan85.Text = txtEan8Sup5.Text;
        dynamicBarcodeEan85.SupplementValue = txtEan8Sup5Sup.Text;
    }

    protected void btnUpdateUpcA_Click(object sender, EventArgs e)
    {
        dynamicBarcodeUpcA.Text = txtUpcA.Text;
    }

    protected void btnUpcA2_Click(object sender, EventArgs e)
    {
        dynamicBarcodeUpcA2.Text = txtUpcASup2.Text;
        dynamicBarcodeUpcA2.SupplementValue = txtUpcASup2Sup.Text;
    }

    protected void btnUpcA5_Click(object sender, EventArgs e)
    {
        dynamicBarcodeUpcA5.Text = txtUpcASup5.Text;
        dynamicBarcodeUpcA5.SupplementValue = txtUpcASup5Sup.Text;
    }

    protected void btnUpdateUpcE_Click(object sender, EventArgs e)
    {
        dynamicBarcodeUpcE.Text = txtUpcE.Text;
    }

    protected void btnUpdateUpcE2_Click(object sender, EventArgs e)
    {
        dynamicBarcodeUpcE2.Text = txtUpcESup2.Text;
        dynamicBarcodeUpcE2.SupplementValue = txtUpcESup2Sup.Text;
    }

    protected void btnUpdateUpcE5_Click(object sender, EventArgs e)
    {
        dynamicBarcodeUpcE5.Text = txtUpcESup5.Text;
        dynamicBarcodeUpcE5.SupplementValue = txtUpcESup5Sup.Text;
    }

    protected void btnUpdateCode11_Click(object sender, EventArgs e)
    {
        dynamicBarcodeCode11.Text = txtCode11.Text;
    }
    protected void btnUpdateGS1_Click(object sender, EventArgs e)
    {
        switch (ddlGS1Type.SelectedValue)
        {
            case "Omnidirectional":
                dynamicBarcodeGS1.GS1DataBarType = ceTe.DynamicBarcode.Creator.GS1DataBarType.Omnidirectional;
```

```
148                 break;
149             case "Limited":
150                 dynamicBarcodeGS1.GS1DataBarType = ceTe.DynamicBarcode.Creator.GS1DataBarType.Limited;
151                 break;
152             case "Expanded":
153                 dynamicBarcodeGS1.GS1DataBarType = ceTe.DynamicBarcode.Creator.GS1DataBarType.Expanded;
154                 break;
155         }
156         dynamicBarcodeGS1.Text = txtGS1DataBar.Text;
157     }
158     protected void btnUpdateStackedGS1_Click(object sender, EventArgs e)
159     {
160         switch (ddlStackedGS1.SelectedValue)
161         {
162             case "Stacked":
163                 dynamicBarcodeStackedGS1.StackedGS1DataBarType = ceTe.DynamicBarcode.Creator.StackedGS1DataBarType.Stacked;
164                 break;
165             case "StackedOmnidirectional":
166                 dynamicBarcodeStackedGS1.StackedGS1DataBarType =
ceTe.DynamicBarcode.Creator.StackedGS1DataBarType.StackedOmnidirectional;
167                 break;
168             case "ExpandedStacked":
169                 dynamicBarcodeStackedGS1.StackedGS1DataBarType =
ceTe.DynamicBarcode.Creator.StackedGS1DataBarType.ExpandedStacked;
170                 break;
171         }
172         dynamicBarcodeStackedGS1.Text = txtStackedGs1.Text;
173     }
174     protected void btnUpdateAustraliaPost_Click(object sender, EventArgs e)
175     {
176         dynamicBarcodeAustraliaPost.Text = txtAustraliaPost.Text;
177     }
178     protected void btnUpdateCode93_Click(object sender, EventArgs e)
179     {
180         dynamicBarcodeCode93.Text = txtCode93.Text;
181     }
182     protected void btnDeutschePostIdentcode_Click(object sender, EventArgs e)
183     {
184         dynamicBarcodeDeutschePostIdentcode.Text = txtDeutschePostIdentcode.Text;
185     }
186     protected void btnDeutschePostLeitcode_Click(object sender, EventArgs e)
187     {
188         dynamicBarcodeDeutschePostLeitcode.Text = txtDeutschePostLeitcode.Text;
189     }
190     protected void btnEan14_Click(object sender, EventArgs e)
191     {
192         dynamicBarcodeEan14.Text = txtEan14.Text;
193     }
194     protected void btnIata25_Click(object sender, EventArgs e)
```

```
    {
        dynamicBarcodeIata25.Text = txtIata25.Text;
    }
    protected void btnIsbnSup5_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIsbnSup5.Text = txtIsbn5Value.Text;
        dynamicBarcodeIsbnSup5.SupplementValue = txtIsbnSup5Value.Text;
    }
    protected void btnIsbnSup2_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIsbnSup2.Text = txtIsbn2Value.Text;
        dynamicBarcodeIsbnSup2.SupplementValue = txtIsbnSup2Value.Text;
    }
    protected void btnIsbn_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIsbn.Text = txtIsbn.Text;
    }
    protected void btnIsmnSup5_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIsmnSup5.Text = txtIsmn5Value.Text;
        dynamicBarcodeIsmnSup5.SupplementValue = txtIsmnSup5Value.Text;
    }
    protected void btnIsmnSup2_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIsmnSup2.Text = txtIsmn2Value.Text;
        dynamicBarcodeIsmnSup2.SupplementValue = txtIsmnSup2Value.Text;
    }
    protected void btnIsmn_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIsmn.Text = txtIsmn.Text;
    }
    protected void btnIssnSup5_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIssnSup5.Text = txtIssn5Value.Text;
        dynamicBarcodeIssnSup5.SupplementValue = txtIssnSup5Value.Text;
    }
    protected void btnIssnSup2_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIssnSup2.Text = txtIssn2Value.Text;
        dynamicBarcodeIssnSup2.SupplementValue = txtIssnSup2Value.Text;
    }
    protected void btnIssn_Click(object sender, EventArgs e)
    {
        dynamicBarcodeIssn.Text = txtIssn.Text;
    }
    protected void btnItf14_Click(object sender, EventArgs e)
    {
        dynamicBarcodeItf14.Text = txtItf14.Text;
    }
```

```
244     protected void btnKix_Click(object sender, EventArgs e)
245     {
246         dynamicBarcodeKix.Text = txtKix.Text;
247     }
248     protected void btnSingaporePost_Click(object sender, EventArgs e)
249     {
250         dynamicBarcodeSingaporePost.Text = txtSingaporePost.Text;
251     }
252     protected void btnAztec_Click(object sender, EventArgs e)
253     {
254         dynamicBarcodeAztec.Text = txtAztec.Text;
255     }
256 }
```