AllBarcodes_Basic.aspx

```
<%@ Page Language="VB" AutoEventWireup="false" CodeFile="AllBarcodes_Basic.aspx.vb"
    Inherits="AllBarcodes_Basic" MaintainScrollPositionOnPostback="true" %>

<%@ Register Assembly="ceTe.DynamicBarcode.Creator.20" Namespace="ceTe.DynamicBarcode.Creator.Web"
    TagPrefix="cc1" %>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml">
<head id="Head1" runat="server">
    <title>DynamicBarcode Creator Examples</title>
    <link rel="stylesheet" type="text/css" href="Style/DynamicBarcodeCreator.css" />
    <meta name="DESCRIPTION" content="All Barcode Example in C# using DynamicBarcode Creator v2.0 for .NET" />
</head>
<body>
    <div id="banner">
        <img alt="DynamicBarcode Creator" height="85px" width="74px" src="Images/DynamicBarcodeCreator.png"
            align="right" /><img height="26px" width="156px" alt="ceTe Software" src="Images/ceTeSoftware_top.gif" />
        <div id="header">
            <i>DynamicBarcode Creator</i> v2.0 for .NET Examples</div>
        <h1>
            All Barcodes Example</h1>
    </div>
    <div id="content">
        <form id="AllBarcodes_Basic" runat="server">
        <table border="0">
            <tr class="head">
                <td style="width: 25%; height: 20px">
                    Barcode Type
                </td>
                <td style="width: 25%; height: 20px">
                    Data
                </td>
                <td style="width: 50%; height: 20px">
                    Barcode Using Controls
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    UPC/EAN/JAN Barcodes
                </td>
            </tr>
            <tr>
```

```
                <td>
                    EAN 13 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtEan13" runat="server" Text="123456789012"></asp:TextBox>
                    <asp:Button ID="btnUpdateEan13" runat="server" Text="Update" OnClick="btnUpdateEan13_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan13" runat="server" LinearBarcodeType="Ean13"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789012" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 13, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup2" runat="server" Text="123456789012"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup2Sup" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateEan132" runat="server" Text="Update" OnClick="btnUpdateEan132_Click" />
                            </td>
                        </tr>
```

```
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan132" runat="server" LinearBarcodeType="Ean13Supplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789012" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 13, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup5" runat="server" Text="123456789012"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan13Sup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateEan135" runat="server" Text="Update" OnClick="btnUpdateEan135_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan135" runat="server" LinearBarcodeType="Ean13Supplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789012" SupplementValue="12345" />
```

```
                </td>
            </tr>
            <tr>
                <td>
                    EAN 8 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtEan8" runat="server" Text="12345670"></asp:TextBox>
                    <asp:Button ID="btnUpdateEan8" runat="server" Text="Update" OnClick="btnUpdateEan8_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan8" runat="server" LinearBarcodeType="Ean8"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345670" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 8, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup2" runat="server" Text="12345670"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup2Sup" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
```

```
                                <asp:Button ID="btnUpdateEan82" runat="server" Text="Update" OnClick="btnUpdateEan82_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan82" runat="server" LinearBarcodeType="Ean8Supplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345670" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 8, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup5" runat="server" Text="12345670"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtEan8Sup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateEan85" runat="server" Text="Update" OnClick="btnUpdateEan85_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
```

```
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan85" runat="server" LinearBarcodeType="Ean8Supplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345670" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version A Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtUpcA" runat="server" Text="12345678901"></asp:TextBox>
                    <asp:Button ID="btnUpdateUpcA" runat="server" Text="Update" OnClick="btnUpdateUpcA_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcA" runat="server" LinearBarcodeType="UpcA"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345678901" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version A, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup2" runat="server" Text="12345678901"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup2Sup" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
```

```
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpcA2" runat="server" Text="Update" OnClick="btnUpcA2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcA2" runat="server" LinearBarcodeType="UpcASupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345678901" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version A, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup5" runat="server" Text="12345678901"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcASup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpcA5" runat="server" Text="Update" OnClick="btnUpcA5_Click" />
                            </td>
```

```
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcA5" runat="server" LinearBarcodeType="UpcASupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="12345678901" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version E Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtUpcE" runat="server" Text="0123456"></asp:TextBox>
                    <asp:Button ID="btnUpdateUpcE" runat="server" Text="Update" OnClick="btnUpdateUpcE_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcE" runat="server" LinearBarcodeType="UpcE"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="0123456" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version E, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup2" runat="server" Text="0123456"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup2Sup" runat="server" Text="12"></asp:TextBox>
```

```
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateUpcE2" runat="server" Text="Update" OnClick="btnUpdateUpcE2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeUpcE2" runat="server" LinearBarcodeType="UpcESupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="0123456" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    UPC Version E, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup5" runat="server" Text="0123456"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtUpcESup5Sup" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
```

```
370                             <td style="padding-left: 120px;">
371                                 <asp:Button ID="btnUpdateUpcE5" runat="server" Text="Update" OnClick="btnUpdateUpcE5_Click" />
372                             </td>
373                         </tr>
374                     </table>
375                 </td>
376                 <td style="width: 193px">
377                     <cc1:LinearBarcode ID="dynamicBarcodeUpcE5" runat="server" LinearBarcodeType="UpcESupplement5"
378                         Dpi="96" BarcodeMargin="20,20,20,20" Text="0123456" SupplementValue="12345" />
379                 </td>
380             </tr>
381             <tr class="head">
382                 <td colspan="3" style="height: 15px;">
383                     Postal Barcodes
384                 </td>
385             </tr>
386             <tr>
387                 <td>
388                     Australia Post Barcode
389                 </td>
390                 <td>
391                     <asp:TextBox ID="txtAustraliaPost" runat="server" Text="1112345678"></asp:TextBox>
392                     <asp:Button ID="btnUpdateAustraliaPost" runat="server" Text="Update" OnClick="btnUpdateAustraliaPost_Click"
/>
393                 </td>
394                 <td style="width: 193px">
395                     <cc1:LinearBarcode ID="dynamicBarcodeAustraliaPost" runat="server" LinearBarcodeType="AustraliaPost"
396                         Dpi="96" BarcodeMargin="20,20,20,20" Text="1112345678" />
397                 </td>
398             </tr>
399             <tr>
400                 <td>
401                     Deutsche Post Identcode Barcode
402                 </td>
403                 <td>
404                     <asp:TextBox ID="txtDeutschePostIdentcode" runat="server" Text="12345678901"></asp:TextBox>
405                     <asp:Button ID="btnDeutschePostIdentcode" runat="server" Text="Update"
OnClick="btnDeutschePostIdentcode_Click" />
406                 </td>
407                 <td style="width: 193px">
408                     <cc1:LinearBarcode ID="dynamicBarcodeDeutschePostIdentcode" runat="server" SymbolHeight="80"
```

```
                        LinearBarcodeType="DeutschePostIdentcode" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="12345678901" />
                </td>
            </tr>
            <tr>
                <td>
                    Deutsche Post Leitcode Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtDeutschePostLeitcode" runat="server" Text="1234567890123"></asp:TextBox>
                    <asp:Button ID="btnDeutschePostLeitcode" runat="server" Text="Update"
OnClick="btnDeutschePostLeitcode_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeDeutschePostLeitcode" runat="server" SymbolHeight="80"
                        LinearBarcodeType="DeutschePostLeitcode" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="1234567890123" />
                </td>
            </tr>
            <tr>
                <td>
                    Intelligent Mail Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtIntelligentMail" runat="server" Text="01234567094987654321012345678901"></asp:TextBox>
                    <asp:Button ID="btnUpdateIntelligentMail" runat="server" Text="Update"
OnClick="btnUpdateIntelligentMail_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIntelligentMail" runat="server"
LinearBarcodeType="IntelligentMailBarcode"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="01234567094987654321012345678901" />
                </td>
            </tr>
            <tr>
                <td>
                    KIX Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtKix" runat="server" Text="1231FZ13XHS"></asp:TextBox>
                    <asp:Button ID="btnKix" runat="server" Text="Update" OnClick="btnKix_Click" />
```

```
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeKix" runat="server" LinearBarcodeType="Kix"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1231FZ13XHS" />
                </td>
            </tr>
            <tr>
                <td>
                    Postnet Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtPostnet" runat="server" Text="20815470412"></asp:TextBox>
                    <asp:Button ID="btnUpdatePostnet" runat="server" Text="Update" OnClick="btnUpdatePostnet_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodePostnet" runat="server" LinearBarcodeType="Postnet"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="20815470412" />
                </td>
            </tr>
            <tr>
                <td>
                    RM4SCC Royal Mail Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtRm4scc" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnUpdateRm4scc" runat="server" Text="Update" OnClick="btnUpdateRm4scc_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeRm4scc" runat="server" LinearBarcodeType="Rm4scc"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    Singapore Post Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtSingaporePost" runat="server" Text="208154"></asp:TextBox>
                    <asp:Button ID="btnSingaporePost" runat="server" Text="Update" OnClick="btnSingaporePost_Click" />
                </td>
                <td style="width: 193px">
```

```
488                     <cc1:LinearBarcode ID="dynamicBarcodeSingaporePost" runat="server" LinearBarcodeType="SingaporePost"
489                         Dpi="96" BarcodeMargin="20,20,20,20" Text="208154" />
490                 </td>
491             </tr>
492             <tr class="head">
493                 <td colspan="3" style="height: 15px;">
494                     ISBN/ISMN/ISSN Barcodes
495                 </td>
496             </tr>
497             <tr>
498                 <td>
499                     ISBN Barcode
500                 </td>
501                 <td>
502                     <asp:TextBox ID="txtIsbn" runat="server" Text="987123456789"></asp:TextBox>
503                     <asp:Button ID="btnIsbn" runat="server" Text="Update" OnClick="btnIsbn_Click" />
504                 </td>
505                 <td style="width: 193px">
506                     <cc1:LinearBarcode ID="dynamicBarcodeIsbn" runat="server" LinearBarcodeType="Isbn"
507                         Dpi="96" BarcodeMargin="20,20,20,20" Text="987123456789" />
508                 </td>
509             </tr>
510             <tr>
511                 <td>
512                     ISBN, 2 Digit Supplement Barcode
513                 </td>
514                 <td>
515                     <table class="propTable">
516                         <tr>
517                             <td>
518                                 Value :
519                             </td>
520                             <td>
521                                 <asp:TextBox ID="txtIsbn2Value" runat="server" Text="987123456789"></asp:TextBox>
522                             </td>
523                         </tr>
524                         <tr>
525                             <td>
526                                 Supplement :
527                             </td>
528                             <td>
```

```
                                <asp:TextBox ID="txtIsbnSup2Value" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIsbnSup2" runat="server" Text="Update" OnClick="btnIsbnSup2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsbnSup2" runat="server" LinearBarcodeType="IsbnSupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="987123456789" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    ISBN, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsbn5Value" runat="server" Text="987123456789"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsbnSup5Value" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
```

```
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIsbnSup5" runat="server" Text="Update" OnClick="btnIsbnSup5_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsbnSup5" runat="server" LinearBarcodeType="IsbnSupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="987123456789" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    ISMN Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtIsmn" runat="server" Text="979-0-1234-5678"></asp:TextBox>
                    <asp:Button ID="btnIsmn" runat="server" Text="Update" OnClick="btnIsmn_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsmn" runat="server" LinearBarcodeType="Ismn"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="979-0-1234-5678" />
                </td>
            </tr>
            <tr>
                <td>
                    ISMN, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsmn2Value" runat="server" Text="979-0-1234-5678"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
```

```
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsmnSup2Value" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIsmnSup2" runat="server" Text="Update" OnClick="btnIsmnSup2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsmnSup2" runat="server" LinearBarcodeType="IsmnSupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="979-0-1234-5678" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    ISMN, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsmn5Value" runat="server" Text="979-0-1234-5678"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIsmnSup5Value" runat="server" Text="12345"></asp:TextBox>
                            </td>
```

```
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIsmnSup5" runat="server" Text="Update" OnClick="btnIsmnSup5_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIsmnSup5" runat="server" LinearBarcodeType="IsmnSupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="979-0-1234-5678" SupplementValue="12345" />
                </td>
            </tr>
            <tr>
                <td>
                    ISSN Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtIssn" runat="server" Text="977-1234-56700"></asp:TextBox>
                    <asp:Button ID="btnIssn" runat="server" Text="Update" OnClick="btnIssn_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIssn" runat="server" LinearBarcodeType="Issn"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="977-1234-56700" />
                </td>
            </tr>
            <tr>
                <td>
                    ISSN, 2 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIssn2Value" runat="server" Text="977-1234-56700"></asp:TextBox>
                            </td>
```

```
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIssnSup2Value" runat="server" Text="12"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIssnSup2" runat="server" Text="Update" OnClick="btnIssnSup2_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIssnSup2" runat="server" LinearBarcodeType="IssnSupplement2"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="977-1234-56700" SupplementValue="12" />
                </td>
            </tr>
            <tr>
                <td>
                    ISSN, 5 Digit Supplement Barcode
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td>
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtIssn5Value" runat="server" Text="977-1234-56700"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                                Supplement :
                            </td>
```

```
                            <td>
                                <asp:TextBox ID="txtIssnSup5Value" runat="server" Text="12345"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td>
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnIssnSup5" runat="server" Text="Update" OnClick="btnIssnSup5_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeIssnSup5" runat="server" LinearBarcodeType="IssnSupplement5"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="977-1234-56700" SupplementValue="12345" />
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    Other Linear Barcodes
                </td>
            </tr>
            <tr>
                <td style="height: 39px">
                    Codabar Barcode
                </td>
                <td style="height: 39px">
                    <asp:TextBox ID="txtCodabar" runat="server" Text="A1234D"></asp:TextBox>
                    <asp:Button ID="btnUpdateCodabar" runat="server" Text="Update" OnClick="btnUpdateCodabar_Click" />
                </td>
                <td style="width: 193px; height: 39px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCodabar" runat="server" SymbolHeight="80" LinearBarcodeType="Codabar"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="A1234D" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 11 Barcode
                </td>
                <td>
```

```
                    <asp:TextBox ID="txtCode11" runat="server" Text="1234567"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode11" runat="server" Text="Update" OnClick="btnUpdateCode11_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode11" runat="server" SymbolHeight="80" LinearBarcodeType="Code11"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 128 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode128" runat="server" Text="Hello World"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode128" runat="server" Text="Update" OnClick="btnUpdateCode128_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode128" runat="server" SymbolHeight="80" LinearBarcodeType="Code128"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="Hello World" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 25 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode25" runat="server" Text="123456789"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode25" runat="server" Text="Update" OnClick="btnUpdateCode25_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode25" runat="server" SymbolHeight="80" LinearBarcodeType="Code25"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 39 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode39" runat="server" Text="123456789"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode39" runat="server" Text="Update" OnClick="btnUpdateCode39_Click" />
```

```
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode39" runat="server" SymbolHeight="80" LinearBarcodeType="Code39"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789" />
                </td>
            </tr>
            <tr>
                <td>
                    Code 93 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtCode93" runat="server" Text="123456789"></asp:TextBox>
                    <asp:Button ID="btnUpdateCode93" runat="server" Text="Update" OnClick="btnUpdateCode93_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeCode93" runat="server" SymbolHeight="80" LinearBarcodeType="Code93"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="123456789" />
                </td>
            </tr>
            <tr>
                <td>
                    EAN 14 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtEan14" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnEan14" runat="server" Text="Update" OnClick="btnEan14_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeEan14" runat="server" SymbolHeight="80" LinearBarcodeType="Ean14"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    GS1 DataBar
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td class="style1">
                                Value :
```

```
                            </td>
                            <td>
                                <asp:TextBox ID="txtGS1DataBar" runat="server" Text="(01)1234567890123"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                                GS1 Type :
                            </td>
                            <td>
                                <asp:DropDownList ID="ddlGS1Type" runat="server">
                                    <asp:ListItem Selected="True" Text="Omnidirectional" Value="Omnidirectional"></asp:ListItem>
                                    <asp:ListItem Text="Limited" Value="Limited"></asp:ListItem>
                                    <asp:ListItem Text="Expanded" Value="Expanded"></asp:ListItem>
                                </asp:DropDownList>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateGS1" runat="server" Text="Update" OnClick="btnUpdateGS1_Click" />
                            </td>
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeGS1" runat="server" LinearBarcodeType="GS1DataBar"
                        GS1DataBarType="Omnidirectional" SymbolHeight="80" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="(01)1234567890123" />
                </td>
            </tr>
            <tr>
                <td>
                    IATA 25 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtIata25" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnIata25" runat="server" Text="Update" OnClick="btnIata25_Click" />
                </td>
                <td style="width: 193px">
```

```
                    <cc1:LinearBarcode ID="dynamicBarcodeIata25" runat="server" SymbolHeight="80" LinearBarcodeType="Iata25"
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    Interleaved 25 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtInterleaved25" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnUpdateInterleaved25" runat="server" Text="Update" OnClick="btnUpdateInterleaved25_Click"
/>
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeInterleaved" runat="server" SymbolHeight="80"
                        LinearBarcodeType="Interleaved25" Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    ITF 14 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtItf14" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnItf14" runat="server" Text="Update" OnClick="btnItf14_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeItf14" runat="server" LinearBarcodeType="Itf14"
                        SymbolHeight="80" Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr>
                <td>
                    MSI Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtMsiBarcode" runat="server" Text="1234567890"></asp:TextBox>
                    <asp:Button ID="btnUpdateMsi" runat="server" Text="Update" OnClick="btnUpdateMsi_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:LinearBarcode ID="dynamicBarcodeMsi" runat="server" SymbolHeight="80" LinearBarcodeType="MsiBarcode"
```

```
                        Dpi="96" BarcodeMargin="20,20,20,20" Text="1234567890" />
                </td>
            </tr>
            <tr class="head">
                <td colspan="3" style="height: 15px;">
                    2D and Stacked GS1 Databar Barcodes
                </td>
            </tr>
            <tr>
                <td>
                    Stacked GS1 DataBar
                </td>
                <td>
                    <table class="propTable">
                        <tr>
                            <td class="style1">
                                Value :
                            </td>
                            <td>
                                <asp:TextBox ID="txtStackedGs1" runat="server" Text="(01)1234567890123"></asp:TextBox>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                                Stacked GS1 Type :
                            </td>
                            <td>
                                <asp:DropDownList ID="ddlStackedGS1" runat="server">
                                    <asp:ListItem Selected="True" Text="Stacked" Value="Stacked"></asp:ListItem>
                                    <asp:ListItem Text="Stacked Omnidirectional" Value="StackedOmnidirectional"></asp:ListItem>
                                    <asp:ListItem Text="Expanded Stacked" Value="ExpandedStacked"></asp:ListItem>
                                </asp:DropDownList>
                            </td>
                        </tr>
                        <tr>
                            <td class="style1">
                            </td>
                            <td style="padding-left: 120px;">
                                <asp:Button ID="btnUpdateStackedGS1" runat="server" Text="Update"
OnClick="btnUpdateStackedGS1_Click" />
                            </td>
```

```
                        </tr>
                    </table>
                </td>
                <td style="width: 193px">
                    <cc1:StackedGS1DataBar ID="dynamicBarcodeStackedGS1" runat="server" StackedGS1DataBarType="Stacked"
                        RowHeight="50" Dpi="96" BarcodeMargin="20,20,20,20" />
                </td>
            </tr>
            <tr>
                <td>
                    Aztec Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtAztec" runat="server" Text="Hello World"></asp:TextBox>
                    <asp:Button ID="btnAztec" runat="server" Text="Update" OnClick="btnAztec_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:Aztec ID="dynamicBarcodeAztec" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Hello World" />
                </td>
            </tr>
            <tr>
                <td>
                    Data Matrix Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtDataMatrix" runat="server" Text="Data Matrix barcode for .NET can handle
overflow."></asp:TextBox>
                    <asp:Button ID="btnUpdateDataMatrix" runat="server" Text="Update" OnClick="btnUpdateDataMatrix_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:DataMatrix ID="dynamicBarcodeDataMatrix" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Data Matrix barcode for .NET can handle overflow." />
                </td>
            </tr>
            <tr>
                <td>
                    PDF417 Barcode
                </td>
                <td>
                    <asp:TextBox ID="txtPdf417" runat="server" Text="Hello World"></asp:TextBox>
```

```
                    <asp:Button ID="btnUpdatePdf417" runat="server" Text="Update" OnClick="btnUpdatePdf417_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:Pdf417 ID="dynamicBarcodePdf417" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Hello World" />
                </td>
            </tr>
            <tr>
                <td>
                    QR Code
                </td>
                <td>
                    <asp:TextBox ID="txtQRCode" runat="server" Text="Hello World"></asp:TextBox>
                    <asp:Button ID="btnUpdateQRCode" runat="server" Text="Update" OnClick="btnUpdateQRCode_Click" />
                </td>
                <td style="width: 193px">
                    <cc1:QRCode ID="dynamicBarcodeQRCode" runat="server" Dpi="96" BarcodeMargin="20,20,20,20"
                        Text="Hello World" />
                </td>
            </tr>
        </table>
        </form>
    </div>
</body>
</html>
```

AllBarcodes_Basic.aspx.vb

```
1
2  Partial Class AllBarcodes_Basic
3      Inherits System.Web.UI.Page
4
5
6      Protected Sub Page_Load(sender As Object, e As System.EventArgs) Handles Me.Load
7
8      End Sub
9
10     Protected Sub btnUpdateCode128_Click(sender As Object, e As System.EventArgs) Handles btnUpdateCode128.Click
11         dynamicBarcodeCode128.Text = txtCode128.Text
12     End Sub
13
14     Protected Sub btnUpdateCodabar_Click(sender As Object, e As System.EventArgs) Handles btnUpdateCodabar.Click
15         dynamicBarcodeCodabar.Text = txtCodabar.Text
16     End Sub
17
18     Protected Sub btnUpdateCode25_Click(sender As Object, e As System.EventArgs) Handles btnUpdateCode25.Click
19         dynamicBarcodeCode25.Text = txtCode25.Text
20     End Sub
21
22     Protected Sub btnUpdateCode39_Click(sender As Object, e As System.EventArgs) Handles btnUpdateCode39.Click
23         dynamicBarcodeCode39.Text = txtCode39.Text
24     End Sub
25
26     Protected Sub btnUpdateDataMatrix_Click(sender As Object, e As System.EventArgs) Handles btnUpdateDataMatrix.Click
27         dynamicBarcodeDataMatrix.Text = txtDataMatrix.Text
28     End Sub
29
30     Protected Sub btnUpdateQRCode_Click(sender As Object, e As System.EventArgs) Handles btnUpdateQRCode.Click
31         dynamicBarcodeQRCode.Text = txtQRCode.Text
32     End Sub
33
34     Protected Sub btnUpdatePdf417_Click(sender As Object, e As System.EventArgs) Handles btnUpdatePdf417.Click
35         dynamicBarcodePdf417.Text = txtPdf417.Text
36     End Sub
37
38     Protected Sub btnUpdateIntelligentMail_Click(sender As Object, e As System.EventArgs) Handles btnUpdateIntelligentMail.Click
39         dynamicBarcodeIntelligentMail.Text = txtIntelligentMail.Text
40     End Sub
41
```

```
    Protected Sub btnUpdatePostnet_Click(sender As Object, e As System.EventArgs) Handles btnUpdatePostnet.Click
        dynamicBarcodePostnet.Text = txtPostnet.Text
    End Sub

    Protected Sub btnUpdateRm4scc_Click(sender As Object, e As System.EventArgs) Handles btnUpdateRm4scc.Click
        dynamicBarcodeRm4scc.Text = txtRm4scc.Text
    End Sub

    Protected Sub btnUpdateInterleaved25_Click(sender As Object, e As System.EventArgs) Handles btnUpdateInterleaved25.Click
        dynamicBarcodeInterleaved.Text = txtInterleaved25.Text
    End Sub

    Protected Sub btnUpdateMsi_Click(sender As Object, e As System.EventArgs) Handles btnUpdateMsi.Click
        dynamicBarcodeMsi.Text = txtMsiBarcode.Text
    End Sub

    Protected Sub btnUpdateEan8_Click(sender As Object, e As System.EventArgs) Handles btnUpdateEan8.Click
        dynamicBarcodeEan8.Text = txtEan8.Text
    End Sub

    Protected Sub btnUpdateEan82_Click(sender As Object, e As System.EventArgs) Handles btnUpdateEan82.Click
        dynamicBarcodeEan82.Text = txtEan8Sup2.Text
        dynamicBarcodeEan82.SupplementValue = txtEan8Sup2Sup.Text
    End Sub

    Protected Sub btnUpdateEan85_Click(sender As Object, e As System.EventArgs) Handles btnUpdateEan85.Click
        dynamicBarcodeEan85.Text = txtEan8Sup5.Text
        dynamicBarcodeEan85.SupplementValue = txtEan8Sup5Sup.Text
    End Sub

    Protected Sub btnUpdateEan13_Click(sender As Object, e As System.EventArgs) Handles btnUpdateEan13.Click
        dynamicBarcodeEan13.Text = txtEan13.Text
    End Sub

    Protected Sub btnUpdateEan132_Click(sender As Object, e As System.EventArgs) Handles btnUpdateEan132.Click
        dynamicBarcodeEan132.Text = txtEan13Sup2.Text
        dynamicBarcodeEan132.SupplementValue = txtEan13Sup2Sup.Text
    End Sub

    Protected Sub btnUpdateEan135_Click(sender As Object, e As System.EventArgs) Handles btnUpdateEan135.Click
        dynamicBarcodeEan135.Text = txtEan13Sup5.Text
```

AllBarcodes_Basic.aspx.vb

```
        dynamicBarcodeEan135.SupplementValue = txtEan13Sup5Sup.Text
    End Sub

    Protected Sub btnUpdateUpcA_Click(sender As Object, e As System.EventArgs) Handles btnUpdateUpcA.Click
        dynamicBarcodeUpcA.Text = txtUpcA.Text
    End Sub

    Protected Sub btnUpcA2_Click(sender As Object, e As System.EventArgs) Handles btnUpcA2.Click
        dynamicBarcodeUpcA2.Text = txtUpcASup2.Text
        dynamicBarcodeUpcA2.SupplementValue = txtUpcASup2Sup.Text
    End Sub

    Protected Sub btnUpcA5_Click(sender As Object, e As System.EventArgs) Handles btnUpcA5.Click
        dynamicBarcodeUpcA5.Text = txtUpcASup5.Text
        dynamicBarcodeUpcA5.SupplementValue = txtUpcASup5Sup.Text
    End Sub

    Protected Sub btnUpdateUpcE_Click(sender As Object, e As System.EventArgs) Handles btnUpdateUpcE.Click
        dynamicBarcodeUpcE.Text = txtUpcE.Text
    End Sub

    Protected Sub btnUpdateUpcE2_Click(sender As Object, e As System.EventArgs) Handles btnUpdateUpcE2.Click
        dynamicBarcodeUpcE2.Text = txtUpcESup2.Text
        dynamicBarcodeUpcE2.SupplementValue = txtUpcESup2Sup.Text
    End Sub

    Protected Sub btnUpdateUpcE5_Click(sender As Object, e As System.EventArgs) Handles btnUpdateUpcE5.Click
        dynamicBarcodeUpcE5.Text = txtUpcESup5.Text
        dynamicBarcodeUpcE5.SupplementValue = txtUpcESup5Sup.Text
    End Sub

    Protected Sub btnUpdateCode11_Click(sender As Object, e As System.EventArgs) Handles btnUpdateCode11.Click
        dynamicBarcodeCode11.Text = txtCode11.Text
    End Sub

    Protected Sub btnUpdateGS1_Click(sender As Object, e As System.EventArgs) Handles btnUpdateGS1.Click
        Select Case (ddlGS1Type.SelectedValue)
            Case "Omnidirectional"
                dynamicBarcodeGS1.GS1DataBarType = ceTe.DynamicBarcode.Creator.GS1DataBarType.Omnidirectional
            Case "Limited"
                dynamicBarcodeGS1.GS1DataBarType = ceTe.DynamicBarcode.Creator.GS1DataBarType.Limited
```

```
124             Case "Expanded"
125                 dynamicBarcodeGS1.GS1DataBarType = ceTe.DynamicBarcode.Creator.GS1DataBarType.Expanded
126         End Select
127         dynamicBarcodeGS1.Text = txtGS1DataBar.Text
128     End Sub
129
130     Protected Sub btnUpdateStackedGS1_Click(sender As Object, e As System.EventArgs) Handles btnUpdateStackedGS1.Click
131         Select Case (ddlStackedGS1.SelectedValue)
132             Case "Stacked"
133                 dynamicBarcodeStackedGS1.StackedGS1DataBarType = ceTe.DynamicBarcode.Creator.StackedGS1DataBarType.Stacked
134             Case "StackedOmnidirectional"
135                 dynamicBarcodeStackedGS1.StackedGS1DataBarType =
ceTe.DynamicBarcode.Creator.StackedGS1DataBarType.StackedOmnidirectional
136             Case "ExpandedStacked"
137                 dynamicBarcodeStackedGS1.StackedGS1DataBarType =
ceTe.DynamicBarcode.Creator.StackedGS1DataBarType.ExpandedStacked
138         End Select
139         dynamicBarcodeStackedGS1.Text = txtStackedGs1.Text
140     End Sub
141
142     Protected Sub btnUpdateAustraliaPost_Click(sender As Object, e As System.EventArgs) Handles btnUpdateAustraliaPost.Click
143         dynamicBarcodeAustraliaPost.Text = txtAustraliaPost.Text
144     End Sub
145
146     Protected Sub btnUpdateCode93_Click(sender As Object, e As System.EventArgs) Handles btnUpdateCode93.Click
147         dynamicBarcodeCode93.Text = txtCode93.Text
148     End Sub
149
150     Protected Sub btnDeutschePostIdentcode_Click(sender As Object, e As System.EventArgs) Handles btnDeutschePostIdentcode.Click
151         dynamicBarcodeDeutschePostIdentcode.Text = txtDeutschePostIdentcode.Text
152     End Sub
153
154     Protected Sub btnDeutschePostLeitcode_Click(sender As Object, e As System.EventArgs) Handles btnDeutschePostLeitcode.Click
155         dynamicBarcodeDeutschePostLeitcode.Text = txtDeutschePostLeitcode.Text
156     End Sub
157
158     Protected Sub btnEan14_Click(sender As Object, e As System.EventArgs) Handles btnEan14.Click
159         dynamicBarcodeEan14.Text = txtEan14.Text
160     End Sub
161
162     Protected Sub btnIata25_Click(sender As Object, e As System.EventArgs) Handles btnIata25.Click
```

```
163         dynamicBarcodeIata25.Text = txtIata25.Text
164     End Sub
165
166     Protected Sub btnIsbn_Click(sender As Object, e As System.EventArgs) Handles btnIsbn.Click
167         dynamicBarcodeIsbn.Text = txtIsbn.Text
168     End Sub
169
170     Protected Sub btnIsbnSup2_Click(sender As Object, e As System.EventArgs) Handles btnIsbnSup2.Click
171         dynamicBarcodeIsbnSup2.Text = txtIsbn2Value.Text
172         dynamicBarcodeIsbnSup2.SupplementValue = txtIsbnSup2Value.Text
173     End Sub
174
175     Protected Sub btnIsbnSup5_Click(sender As Object, e As System.EventArgs) Handles btnIsbnSup5.Click
176         dynamicBarcodeIsbnSup5.Text = txtIsbn5Value.Text
177         dynamicBarcodeIsbnSup5.SupplementValue = txtIsbnSup5Value.Text
178     End Sub
179
180     Protected Sub btnIsmn_Click(sender As Object, e As System.EventArgs) Handles btnIsmn.Click
181         dynamicBarcodeIsmn.Text = txtIsmn.Text
182     End Sub
183
184     Protected Sub btnIsmnSup2_Click(sender As Object, e As System.EventArgs) Handles btnIsmnSup2.Click
185         dynamicBarcodeIsmnSup2.Text = txtIsmn2Value.Text
186         dynamicBarcodeIsmnSup2.SupplementValue = txtIsmnSup2Value.Text
187     End Sub
188
189     Protected Sub btnIsmnSup5_Click(sender As Object, e As System.EventArgs) Handles btnIsmnSup5.Click
190         dynamicBarcodeIsmnSup5.Text = txtIsmn5Value.Text
191         dynamicBarcodeIsmnSup5.SupplementValue = txtIsmnSup5Value.Text
192     End Sub
193
194     Protected Sub btnIssn_Click(sender As Object, e As System.EventArgs) Handles btnIssn.Click
195         dynamicBarcodeIssn.Text = txtIssn.Text
196     End Sub
197
198     Protected Sub btnIssnSup2_Click(sender As Object, e As System.EventArgs) Handles btnIssnSup2.Click
199         dynamicBarcodeIssnSup2.Text = txtIssn2Value.Text
200         dynamicBarcodeIssnSup2.SupplementValue = txtIssnSup2Value.Text
201     End Sub
202
203     Protected Sub btnIssnSup5_Click(sender As Object, e As System.EventArgs) Handles btnIssnSup5.Click
```

```
        dynamicBarcodeIssnSup5.Text = txtIssn5Value.Text
        dynamicBarcodeIssnSup5.SupplementValue = txtIssnSup5Value.Text
    End Sub

    Protected Sub btnItf14_Click(sender As Object, e As System.EventArgs) Handles btnItf14.Click
        dynamicBarcodeItf14.Text = txtItf14.Text
    End Sub

    Protected Sub btnKix_Click(sender As Object, e As System.EventArgs) Handles btnKix.Click
        dynamicBarcodeKix.Text = txtKix.Text
    End Sub

    Protected Sub btnSingaporePost_Click(sender As Object, e As System.EventArgs) Handles btnSingaporePost.Click
        dynamicBarcodeSingaporePost.Text = txtSingaporePost.Text
    End Sub

    Protected Sub btnAztec_Click(sender As Object, e As System.EventArgs) Handles btnAztec.Click
        dynamicBarcodeAztec.Text = txtAztec.Text
    End Sub
End Class
```